CPP326-C/ACM

48x40 (Standard) **Plastic Industrial Pallet**

Technical Data

Dimensions Weight

Truckload Qty

Stack TL / LTL

48x40x5.9 inches (1219x1016x150 mm) 35.0 lbs

Load Capacities	
Static	17600 lbs
Dynamic	5300 lbs
Racking	1300 lbs
Entry	4-way

300 lbs 300 lbs -way 540

18 / 16

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors. _____

Handling Data

Nestable No

Stackable Yes

Rackable Yes

Reusability One-Way Destination Export

Airfreight No

ISPM-15 Exempt Yes

Food Grade Yes, non-FDA

Pharmaceutical Yes





Materials and Colors

Condition New

Material ACM (Recycled)

Color Black

Deck Specs

Top Deck Closed

Bottom Deck 6 Runner - Perimeter+2 Cross (cruciform perimeter base)

Available Options: Open Top = CPP32# Closed Top = CPP32#-C

CPP320 - No skids (nestable) CPP323 - 3 Runner snap-on skids* CPP326 - 6 Runner snap-on skids* *Order with skids off for lower shipping cost

Features

- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items (not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- . Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Spec Sheet Generated On: 6/1/2024

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.