

CPP336/ACM

48x40 (Standard) Plastic Industrial Pallet



Technical Data

Dimensions 48x40x5.9 inches (1219x1016x150 mm)
Weight 33.0 lbs

Load Capacities

Static 8500 lbs
Dynamic 4400 lbs
Racking 650 lbs

Entry 4-way
Truckload Qty 540
Stack TL / LTL 18 / 16

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No	Reusability One-Way	ISPM-15 Exempt Yes
Stackable Yes	Destination Export	Food Grade No
Rackable Yes	Airfreight No	Pharmaceutical Yes

Materials and Colors

Condition
New

Material
ACM (Recycled)

Color
Black

Deck Specs

Top Deck
Open

Bottom Deck
6 Runner - Perimeter+2 Cross
(cruciform perimeter base)

Available Options:

CPP330 - No skids (nestable)
CPP333 - 3 Runner snap-on skids*
CPP336 - 6 Runner snap-on skids*
*Order with skids off for lower shipping cost

Features

- Allows for safe double stacking
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



NelsonTM

The Nelson Company
(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com




www.NelsonTechCenter.com

CPP336/ACM

48x40 (Standard)
Plastic Industrial Pallet



Technical Drawings



Nelson™

The Nelson Company
(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com

www.NelsonTechCenter.com

Tech Sheet Generated On: 5/20/2024

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.