PS4840FP-ProFM

48x40 (Standard) **Plastic Industrial Pallet**

Technical Data

Dimensions 48x40x5.12 inches

Weight 43.5 lbs

Load Capacities

30000 lbs Static Dynamic 4000 lbs ST Req Racking

4-way Entry Truckload Qty 600 20 / 18 Stack TL / LTL

Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable Reusability No Multi-Trip

Stackable Destination Captive

Rackable Airfreight

Yes

ISPM-15 Exempt

Food Grade FDA Approved

Pharmaceutical

Yes





Materials and Colors

Condition New

Material Color

HDPF Blue, Black, Gray

(High-Density Polyethylene)

Deck Specs

Top Deck Open

Bottom Deck

6 Runner - Perimeter+2 Cross (cruciform perimeter base)

Features

FM approved options available for meeting fire rating requirements.

- Built for safe transportation and storage of pharmaceutical products.
- Meets decaBDE-free fire retardant standards
- Thicker leg design for better impact protection
- · Larger tapered forklift pockets
- Allows for safe double stacking
- Sanitary choice for strict drug manufacturing requirements
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations




www.NelsonTechCenter.com


PS4840FP-ProFM


48x40 (Standard)
Plastic Industrial Pallet



Technical Drawings







SI			

DIM "A"	DIM "B"	DIM "C"	DIM "D"	DIM "E"	DIM "F"	DIM "G"	DIM "H"	DIM "J"	DIM "K"	DIM "L"
48.062	40.052	6.068	10.073	7.76	10.113	13.818	7.009	.751	3.630	5.132

TOLERANCE (+/-) 0.005 BASE PLUS .0025 PER INCH

