# **UP-4840-N-320ACMCD**

# 48x40 (Standard) Plastic Industrial Pallet

#### **Technical Data**

Dimensions Weight	48x40x5.5 inches 23.0 lbs	(1219x1016x140 mm)
<b>Load Capacities</b> Static Dynamic Racking	8800 lbs 2800 lbs 	
Entry Truckload Qty Stack TL	4-way 1800 60	

Load capacities for used pallets may be unavailable or may have changed since issued. Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

**Nestable** Yes

Stackable

Rackable

No

No

Reusability One-Way Destination

Export

Yes

Airfreight

ISPM-15 Exempt Yes

Food Grade Yes, non-FDA

Pharmaceutical Yes



### Materials and Colors

Condition Used

Material ACM (Recycled)

**Color** Varies

Colors and manufacturers vary and orders may be mixed. To avoid return freight charges ask your Sales Rep about special requests. All used pallets have been inspected and cleaned. Pallets may have limited cosmetic damage, but all are structurally sound.

## **Deck Specs**

Top Deck Closed

Bottom Deck 9 Feet - Nesting

#### Features

Structurally sound but slightly irregular pallets. Color varies (black, gray or light gray.) Some pallets have "short shots" (very small gaps where plastic didn't quite fill the mold).

- 13% more per stack (60 vs 52): less floor space, more in a truckload = less inbound freight
- Angled sides for easier fork time access when splitting the stack
- Notch on the side for stretch wrap hook
- New handle cut into the top deck for easier handling
- Nesting saves storage & shipping costs
- Low-cost Plastic Pallet
- Easy-to-clean hygienic design
- Suitable for packaged food items (not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Spec Sheet Generated On: 5/19/2024

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.