CPP326/PE

48x40 (Standard) **Plastic Industrial Pallet**



Technical Data

Dimensions 48x40x5.9 inches (1219x1016x150 mm)

Weight 28.0 lbs

Load Capacities

17600 lbs Static Dynamic 5300 lbs Racking 1300 lbs

4-way Entry Truckload Qty 540 18 / 16 Stack TL / LTL

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable Reusability No Multi-Trip

Stackable Destination Yes Captive

Rackable Airfreight

Yes

Materials and Colors

Condition New

Material Color HDPE/PP (Recycled) Black HDPE/PP (Virgin*) Gray/Custom*

(High-Density Polyethylene/Polypropylene)

*Custom colors and markings available in virgin material. (Minimum quantities required.)

Deck Specs

Top Deck Open

Bottom Deck

6 Runner - Perimeter+2 Cross (cruciform perimeter base)

Available Options: Open Top = CPP32# Closed Top = CPP32#-C

CPP320 - No skids (nestable) CPP323 - 3 Runner snap-on skids* CPP326 - 6 Runner snap-on skids*
*Order with skids off for lower shipping cost





Features

- Allows for safe double stacking
- · Easy-to-clean hygienic design
- · Suitable for packaged food items (not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew · Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



(443) 649-5294 plastic@NelsonCompany.com www.NelsonCompany.com www.NelsonTechCenter.com

ISPM-15 Exempt

Food Grade

Yes, non-FDA

Pharmaceutical

Yes