

CPP326-C/PE

48x40 (Standard) Plastic Industrial Pallet



Technical Data

Dimensions 48x40x5.9 inches (1219x1016x150 mm)
Weight 32.5 lbs

Load Capacities

Static 17600 lbs
Dynamic 5300 lbs
Racking 1300 lbs

Entry 4-way
Truckload Qty 540
Stack TL / LTL 18 / 16

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

| | | |
|-------------------------|----------------------------------|-----------------------------------|
| Nestable No | Reusability Multi-Trip | ISPM-15 Exempt Yes |
| Stackable Yes | Destination Captive | Food Grade Yes, non-FDA |
| Rackable Yes | Airfreight No | Pharmaceutical Yes |

Materials and Colors

Condition
New

| | |
|--|---------------------------------------|
| Material HDPE/PP (Recycled) HDPE/PP (Virgin*) | Color Black Gray/Custom* |
|--|---------------------------------------|

(High-Density Polyethylene/Polypropylene)

*Custom colors and markings available in virgin material.
(Minimum quantities required.)

Deck Specs

Top Deck
Closed

Bottom Deck
6 Runner - Perimeter+2 Cross
(cruciform perimeter base)

Available Options:
Open Top = CPP32#
Closed Top = CPP32#-C

CPP320 - No skids (nestable)
CPP323 - 3 Runner snap-on skids*
CPP326 - 6 Runner snap-on skids*
*Order with skids off for lower shipping cost

Features

- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items
(not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Nelson™

The Nelson Company

(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com

www.NelsonTechCenter.com