# UP-4840-3R-GLExNest

# 48x40 (Standard) **Plastic Industrial Pallet**

#### **Technical Data**

Dimensions	48x40x6.25 inches
Weight	24.0 lbs
<b>Load Capacities</b> Static Dynamic Racking	4000 lbs 2000 lbs
Entry	4-way
Truckload Qty	480
Stack TL	16

Load capacities for used pallets may be unavailable or may have changed since issued. Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) quantities are approximate and may vary by transport equipment or other factors. 

#### **Handling Data**

Nestable No

Stackable

Rackable

Yes

No

Reusability

Multi-Trip Destination Captive & Export

Airfreight Yes

Yes **Food Grade** Yes, non-FDA

**ISPM-15** Exempt

**Pharmaceutical** Yes



New product image shown for illustrative purposes only. Actual product is in used condition.



### **Materials and Colors**

Condition Used

Material HDPE/PP (Recycled)

Color Varies

Colors and manufacturers vary and orders may be mixed. To avoid return freight charges ask your Sales Rep about special requests. All used pallets have been inspected and cleaned. Pallets may have limited cosmetic damage, but all are structurally sound. 

# **Deck Specs**

**Top Deck** Open

**Bottom Deck** 3 Runner - Unidirectional Long Side

-	_	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	Sr	~ ~	0	~	~	~ 1		10	~	l.r	~ /	-		in		t -	11	5.4															
	31	Id	μ-	0		SI	(10	12	d		e	10	У	11	15	ιa	IIE	=u															
_	-	-	_	-	_	-	-	-	-	_	-	-	_	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

# **Features**

- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items (not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Spec Sheet Generated On: 6/1/2024

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.