

UP-4840-3R-CTCX-PORT

48x40 (Standard) Plastic Industrial Pallet



Technical Data

Dimensions 48x40X6 inches
Weight 28 lbs

Load Capacities

Static 6600 lbs
Dynamic 2200 lbs
Racking ST Req

Entry 4-way
Truckload Qty 480
Stack TL 16

Load capacities for used pallets may be unavailable or may have changed since issued. Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No	Reusability One-Way & Multi-Trip	ISPM-15 Exempt Yes
Stackable Yes	Destination Captive & Export	Food Grade Yes, non-FDA
Rackable Yes	Airfreight Yes	Pharmaceutical Yes

Materials and Colors

Condition
Used

Material
HDPE/PP (Recycled)

Color
Varies

(Durable B-Grade)

Colors and manufacturers vary and orders may be mixed. To avoid return freight charges ask your Sales Rep about special requests. All used pallets have been inspected and cleaned. Pallets may have limited cosmetic damage, but all are structurally sound.

Deck Specs

Top Deck
Closed

Bottom Deck
3 Runner - Unidirectional Long Side

Features

Durable B-Grade material includes black colorant. Impact modifiers are added to create a more flexible pallet capable of withstanding harsher handling environments and multiple trips.

- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items
(not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



NelsonTM

The Nelson Company

(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com

www.NelsonTechCenter.com