UP-1120-FP-HO4Lip

44x44 (Square) Plastic Industrial Pallet

Technical Data

Dimensions Weight	44x44x4.1 inches 15 lbs	(1120x1120x105 mm)
Load Capacities Static Dynamic Racking	6500 lbs 2200 lbs ST Req	
Entry Truckload Qty Stack TL / LTL	4-way 644 / 23	

Load capacities for used pallets may be unavailable or may have changed since issued. Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No

Stackable

Rackable

Yes

Yes

Reusability One-Way & Multi-Trip Destination

Captive & Export

Airfreight

Yes

ISPM-15 Exempt Yes

Food Grade Yes, non-FDA

Pharmaceutical Yes





Spec Sheet Generated On: 6/1/2024

Specs subject to change without notice. Provided for informational purposes only. Technical data are guideline values and may vary based on intended use, features, raw materials and environment. Nothing shall be construed as warranties or guarantees, express or implied, regarding products or their use, application, performance or otherwise.



Materials and Colors

Condition Used

Material HDPE	

Color Varies

(High-Density Polyethylene)

Colors and manufacturers vary and orders may be mixed. To avoid return freight charges ask your Sales Rep about special requests. All used pallets have been inspected and cleaned. Pallets may have limited cosmetic damage, but all are structurally sound.

Deck Specs

Top Deck Open

Bottom Deck 6 Runner - Perimeter+2 Cross

(cruciform perimeter base)

Features

- Deck has raised lips (tabs) on corners and all sides
- Can grind lips to reduce pallet height to 4 1/8"
- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items (not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations

