

PG-4840-FP-140US

48x40 (Standard) Plastic Industrial Pallet



Technical Data

Dimensions 48x40x6 inches (1219x1016x152 mm)
Weight 25.0 lbs

Load Capacities

Static 7054 lbs
Dynamic 3858 lbs
Racking 1102 lbs

Entry 4-way
Truckload Qty 540
Stack TL / LTL 18 / 16

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable No	Reusability Multi-Trip	ISPM-15 Exempt Yes
Stackable Yes	Destination Captive	Food Grade Yes, non-FDA
Rackable Yes	Airfreight Yes	Pharmaceutical Yes

Materials and Colors

Condition
New

Material HDPP (Recycled) **Color** Black (custom colors available)

(High-Density Polypropylene)

Deck Specs

Top Deck
Open

Bottom Deck
6 Runner - Perimeter+2 Cross
(cruciform perimeter base)

Available Options:
Top Safety Rim (raised lip)
Anti-Slip Grommets
Individual Markings

Features

Ideal for closed loops or distribution chains across industry sectors.

- Meets GMA standards
- Suitable for automation
- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items
(not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



Nelson™

The Nelson Company

(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com


www.NelsonTechCenter.com

PG-4840-FP-140US

48x40 (Standard)
Plastic Industrial Pallet



Technical Drawings



NelsonTM

The Nelson Company

(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com

www.NelsonTechCenter.com