

CPP320/ACM

48x40 (Standard) Plastic Industrial Pallet



Technical Data

Dimensions 48x40x5.5 inches (1219x1016x140 mm)
Weight 20.0 lbs

Load Capacities

Static 8800 lbs
Dynamic 2800 lbs
Racking --

Entry 4-way
Pallets per Stack 60
Truckload Qty 1800

Available in Truckload or LTL quantities. Minimum quantity required. We reserve the right to change any stated information without prior notice. Not responsible for typographical errors.

Handling Data

Nestable
Yes

Reusability
One-Way

ISPM-15 Exempt
Yes

Stackable
No

Destination
Export

Rackable
No

Airfreight
Yes

Food Grade
Yes, non-FDA

Pharmaceutical
Yes



Materials and Colors

Condition
New

Material
ACM (Recycled)

Color
Black

Deck Specs

Top Deck
Open

Bottom Deck
9 Feet - Nesting

Available Options:

Open Top = CPP32#
Closed Top = CPP32#-C

CPP320 - No skids (nestable)
CPP323 - 3 Runner snap-on skids*
CPP326 - 6 Runner snap-on skids*
*Order with skids off for lower shipping cost

Features

- Lightweight and low height
- 13% more per stack (60 vs 52): less floor space, more in a truckload = less inbound freight
- Angled sides for easier fork time access when splitting the stack
- Notch on the side for stretch wrap hook
- Nesting saves storage & shipping costs
- Low-cost Plastic Pallet
- Easy-to-clean hygienic design
- Suitable for packaged food items
(not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations

Spec Sheet Generated On: 1/28/2023

Specifications subject to change without notice.

Contents of this document are presented for general informational purposes only. Technical data are guideline values based on experience and tests under defined conditions. The data may vary based on intended use, product features, raw materials used and environmental influences. Nothing in this document shall be construed as warranties or guarantees, express or implied, regarding the products or their use, application, performance or otherwise.

Nelson™

The Nelson Company

(443) 649-5294

plastic@NelsonCompany.com

www.NelsonCompany.com

www.NelsonTechCenter.com