

# NPP-4840-FP-ENUS8-OD

## 48x40 (Standard) Plastic Industrial Pallet



### Technical Data

Dimensions 48x40x6.0 inches (1219x1016x152 mm)  
Weight 46.0 lbs

#### Load Capacities


Static 14100 lbs  
Dynamic 4400 lbs  
Racking 2200 lbs

Entry 4-way  
Truckload Qty 510  
Stack TL / LTL 17 / 16

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

### Handling Data

<b>Nestable</b> No	<b>Reusability</b> Multi-Trip	<b>ISPM-15 Exempt</b> Yes
<b>Stackable</b> Yes	<b>Destination</b> Captive	<b>Food Grade</b> Yes, non-FDA
<b>Rackable</b> Yes	<b>Airfreight</b> Yes	<b>Pharmaceutical</b> Yes



### Materials and Colors

**Condition**  
New

**Material** PPM (Recycled) **Color** Black

(High-Density Polypropylene Mix)

### Deck Specs

#### Top Deck

Closed

Note: top deck includes vents and is not a true solid top.

#### Bottom Deck

6 Runner - Perimeter+2 Cross  
(cruciform perimeter base)

#### Available Options:

Top and Bottom Grommets (recommended with freezer use)

### Features

- Top Safety Rim
- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items  
(not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations

# Nelson™

The Nelson Company

(443) 649-5294

[plastic@NelsonCompany.com](mailto:plastic@NelsonCompany.com)

[www.NelsonCompany.com](http://www.NelsonCompany.com)

[www.NelsonTechCenter.com](http://www.NelsonTechCenter.com)