UP-1280-3R-CD40LBS

48x32 (Euro) Plastic Industrial Pallet

Technical Data

Dimensions 47.25x31.25x6 inches (1200x800x150 mm)

Weight 40 lbs

Load Capacities

Static 15000 lbs
Dynamic 3000 lbs
Racking ST Req

Entry 4-way
Truckload Qty 624
Stack TL / LTL -- / 16

Load capacities for used pallets may be unavailable or may have changed since issued. Unit load Sample Tests (ST) are recommended to confirm successful use with specific applications and equipment. TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

Handling Data

Nestable

No

Reusability One-Way & Multi-Trip

One-way & wulli-inp

Stackable Destination
Yes Captive & Export

Rackable Airfreight

Yes No

ISPM-15 Exempt

Yes

Food Grade

Yes, non-FDA

Pharmaceutical

Yes





Materials and Colors

Condition Used

MaterialColorHDPE/PPVaries

(High-Density Polyethylene/Polypropylene)

Colors and manufacturers vary and orders may be mixed. To avoid return freight charges ask your Sales Rep about special requests. All used pallets have been inspected and cleaned. Pallets may have limited cosmetic damage, but all are structurally sound.

Deck Specs

Top Deck Closed

Bottom Deck

3 Runner - Unidirectional Long Side

Features

Mixed load of various colors, mostly black.

- Standard size used across EU
- Design is popular in rail freight applications
- Allows for safe double stacking
- Easy-to-clean hygienic design
- Suitable for packaged food items (not approved for direct food contact)
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



plastic@NelsonCompany.com www.NelsonCompany.com www.NelsonTechCenter.com