

# CP-1280-3R-Ene7CD-NL

48x32 (Euro)

Plastic Industrial Pallet



## Technical Data

Dimensions 47.2x31.5x6.2 inches (1200x800x157 mm)  
Weight 39.5 lbs

### Load Capacities

Static 8800 lbs  
Dynamic 4400 lbs  
Racking 2200 lbs

Entry 4-way  
Truckload Qty 874  
Stack TL / LTL 23 / 15

TL (truckload) and LTL (less-than-truckload) quantities are approximate and may vary by transport equipment or other factors.

## Handling Data

<b>Nestable</b> No	<b>Reusability</b> Multi-Trip	<b>ISPM-15 Exempt</b> Yes
<b>Stackable</b> Yes	<b>Destination</b> Captive & Export	<b>Food Grade</b> No
<b>Rackable</b> Yes	<b>Airfreight</b> Yes	<b>Pharmaceutical</b> Yes

## Materials and Colors

**Condition**  
New

<b>Material</b> HDPE/PP (Recycled) HDPE/PP (Virgin*)	<b>Color</b> Black Gray/Custom*
--	---------------------------------------

(High-Density Polyethylene/Polypropylene)

\*Custom colors and markings available in virgin material.  
(Minimum quantities required.)

## Deck Specs

**Top Deck**  
Closed

**Bottom Deck**  
3 Runner - Unidirectional Long Side

**SHIP FROM**  
**Mfg Plant**  
506 SeaCont (40') / 23 per Inverted Stack  
**US Facility**  
874 TL (53') / 23 per Inverted Stack  
608 TL (53') / 16 per Stack  
LTL 15 per Stack or 23 per Inverted Stack

## Features

**Note:** CP-1280-3R-Ene7CD-NL was previously known as NPP-1280-3R-Ene7CD-NL

Ideal for closed loops or distribution chains across industry sectors including Electronics, Food, Retail, Medical + Pharma (FDA blue, red, green colors available)

- Excellent choice for a high-traffic systems pallet
- Closed deck design eliminates debris getting caught in the pallet
- Anti-slip grommets available
- Standard size used across EU
- Design is popular in rail freight applications
- Allows for safe double stacking
- Sanitary choice for many pharmaceutical applications
- Impervious to acids, fats, solvents and odors
- Resists water absorption & bacteria growth
- Inert to infestation, mold and mildew
- Consistently dimensionally accurate
- Exempt from ISPM 15 shipping regulations



**Nelson**™

The Nelson Company  
(443) 649-5294

[plastic@NelsonCompany.com](mailto:plastic@NelsonCompany.com)  
[www.NelsonCompany.com](http://www.NelsonCompany.com)  
[www.NelsonTechCenter.com](http://www.NelsonTechCenter.com)